

Spot Cooling



Extend the Life
of Your Equipment

| | |
|-----------------------|--|
| Complete Kit | OD1232-SPOT / DIN Part Number - 124141794 Includes: 120x32mm Fan * DIN rail DIN mount fan bracket Mounting screws 2 fan guards Power adaptor with 6' cord Automotive grade, double-sided, mount anywhere tape |
| Spot Cooler Only | OD1232-SPOT Part Number - 124141794 Includes: 120x32mm Fan * 1 fan guard Power adaptor with 6' cord |
| Fan ID | OD1232-12HB-03 * |
| VOLTAGE INPUT | 120VAC / 60Hz |
| INPUT POWER | 19 Watts |
| DC Nominal Current | 0.60 A |
| DC Locked Current | 0.05 A |
| Rated Speed (RPM) | 3750 Max. (40C) |
| Airflow | 65CFM @ 25C / 120CFM @ 40C |
| Noise Level (dB) | 20 ~ 47 |
| Max. Static Pressure | 0.43" H ₂ O |
| Bearing System | Dual Ball |
| Frame & Impeller | PBT, UL94V-O plastic |
| Motor | Brushless DC, auto restart, polarity protected. Thermal Control. |
| Bearing System | Dual ball bearing |
| Insulation Resistance | 10M ohm between leadwire and frame (500VDC) |
| Dielectric Strength | 5mA max at 1500VAC for 1 minute between the leadwire and frame |
| Operation Temperature | -10C ~ +70C |
| Life (L10) | 60,000 hours |

Thermal Speed Control
Airflow Range

65 CFM at 25C
120 CFM at 40C

Energy Saving Solution for your
Green Initiative

*Clips to standard
DIN rail*




*Plugs into any
115VAC power
source*

OD1232-SPOT / DIN

Part Number - 124141794
120x32mm
Thermally controlled Fan *
6' Cord with adaptor
2 guards (1 installed)
DIN rail
DIN mount fan bracket
Mounting screws
Automotive grade, double-sided,
mount anywhere tape

OD1232-SPOT

Part Number - 124141794
120x32mm
Thermally controlled Fan *
6' Cord with adaptor
1 guard installed



OD9225-SPOT - Instant smart cooling
for small spaces is also available in a
smaller package

Part Number - 193141791
92x25mm thermally controlled fan.
[50CFM (3100RPM) at 34C to
< 30CFM (1600RPM) at 22C]
6' cord with adaptor
1 guard installed



Patent Pending